Hand Held Security Metal Detector Tender Specifications Requirement ThruScan HHMD

- 1) Light and suitable to carry in one hand. Rapidly detects metal objects on people who caused alarm on the Walk Through Metal Detector after a manual scan. In addition the detector structure should allow usage to scan letters, packages and boxes.
- 2) Allows operating with headphones.
- 3) Hand Held Metal Detector battery (or chargeable battery) is replaceable without using any tools. The battery specification is documented that it is a chargeable battery.
- 4) Low battery indication, ON-OFF status of the detector and metal detection status with LED's.
- 5) Does not have effects on pace makers, pregnant women and children.
- 6) Selection of audible, visual or if required vibration indication.
- 7) Maximum detector weight of 500 grams.
- 8) Minimum operation duration of 40 hours.
- 9) Maximum length of 50 cm, including the handle
- 10) Normal operation in temperatures between -20 $^{\circ}$ C + 70 $^{\circ}$ C and 95% humidity, IP53 protection.
- 11) PCB's have to be produced using latest surface mounting technology, with very low rate possibility of problems / issues.
- 12) Circuit protection against incorrect connection of the battery to be provided in the detector.
- 13) The detector has to be made of strong ABS material able to absorb hits, drops and slam impacts. Heavy duty frame rugged high impact case with reinforced coil compartment.
- 14) 2 years manufacturer's warranty.
- 15) CE certified and complies with EN 61000-6-3, EN61000-6-2 (TS2418 EN61010-1) norms, ISO 9001:2008 QMS.
- 16) Certified safe by IEEE C95.1-2005 Human Exposure to Electromagnetic Fields.
- 17) In compliance with Safety and EMC Tests.
- 18) Manufactured in compliance with ECAC (European Civil Aviation Conference) criteria's and able to be used for screening of people at airports fulfilling the ECAC requirements.

- 19) Must have Special Design to prevent false alarms caused by the effects from Walkie-Talkies (radio frequencies).
- 20) Hand Held Metal Detector has to be able to detect Test Objects at Min. distances as follows:

Pistol Browning 14 at 17 cm
Pistol C2 Model 75B at 15 cm
Paper Blade (18x100 mm) at 6 cm
Copper Tube (6cm) at 5 cm
9 mm Bullet (Pistol) at 5 cm
Razor Blade at 5 cm
Cable (2 x 1.5mm - 30cm) at 3 cm

Power Requirements:

Operation Voltage: 9V – Alkaline or Ni-Mh Re-Chargeable Battery

Current: Max 5 mA Stand By - 13 mA Alarm

Charger: Mains: 220V AC 50Hz - 12V DC 110mA

21) The Hand Held Metal Detector Should be provided with accessories such as Handle, Carry Bag etc.

22) The alarm sound should be loud.